

Horn Mountain Offshore Oil Field Case Study

August 31, 2020 DOE/NETL-2020/2615



Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference therein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed therein do not necessarily state or reflect those of the United States Government or any agency thereof.

All images in this report were created by NETL, unless otherwise noted.

Horn Mountain Offshore Oil Field Case Study

Vello A. Kuuskraa, Anne Oudinot, and Matt Wallace

¹Advanced Resources International (ARI)

The reviewers and editors for this report were:

Allison Guinan, Leidos Hannah Hoffman, KeyLogic Systems, LLC Donald Remson, NETL SubCLIN COR Travis Warner, KeyLogic Systems, LLC

The contacts for this report are:

Donald Remson
NETL SubCLIN COR
412.386.5379
donald.remson@netl.doe.gov

Derek VikaraKeyLogic Systems, LLC
412.386.7409
derek.vikara@netl.doe.gov

Allison Guinan Leidos 412.386.6855 allison.guinan@netl.doe.gov

The authors wish to acknowledge the excellent guidance, contributions, and cooperation of NETL staff, particularly:

David Morgan, NETL Technical Project Monitor **Timothy Grant**, NETL Technical Project Monitor

This report was prepared by MESA for the U.S. DOE NETL. This work was completed under DOE NETL Contract Number DE-FE0025912. This work was performed under MESA Activity 205.002.

The suggested citation for this report in literature is as follows:

Kuuskraa, V., Oudinot, A., and Wallace, M., "Horn Mountain Offshore Oil Field Case Study," National Energy Technology Laboratory, Pittsburgh, PA, United States, July 31, 2020.




TABLE OF CONTENTS

List of Exhibits	ii
Acronyms and Abbreviations	iv
1 Introduction	1
2 Horn Mountain Oil Field	2
2.1 Structural Setting	3
2.2 Horn Mountain Oil Resources	5
3 Horn Mountain NFB M Sand	6
4 Reservoir Model for the Horn Mountain Oil Field N	NFB M Sand11
4.1 Constructing the Reservoir Model	11
4.2 Calibrating the Reservoir Model	12
5 GEM Modeling the Performance of the CO ₂ Floor	od, Horn Mountain Oil Field NFB M
Sand	15
5.1 CO ₂ Flood Design	15
5.2 Calculated Oil Recovery	16
5.3 Calculated CO ₂ Injection, Production, and S	
6 Modeling the Performance of the Horn Mountai with CO ₂ Prophet Model	
6.1 Use of Dykstra-Parsons (DP) to Capture Feat	ures Not Available in the CO2
Prophet Model	
6.2 CO ₂ Flood Design	28
6.3 Calculated Oil Recovery	28
6.4 CO ₂ Injection, Production, and Storage	28
7 Comparative Analysis of GEM and CO ₂ Prophet Mountain Oil Field NFB M Sand	
8 References	
Appendix A	33
Appendix B	36

LIST OF EXHIBITS

Exhibit 2-1. Location of Horn Mountain oil field, Central GOM	2
Exhibit 2-2. Potential CO ₂ pipeline system for Horn Mountain oil field, Central GOM	
Exhibit 2-3. Hom Mountain M Sand well locations, structural features, and fault blocks.	
Exhibit 2-4. Hom Mountain J Sand and M Sand and well locations	
Exhibit 2-5. Horn Mountain oil resources, cumulative production, and remaining reserv	'es
Exhibit 3-1. Hom Mountain NFB M Sand oil production and water injection wells	
Exhibit 3-2. Reservoir properties, Hom Mountain NFB M Sand	
Exhibit 3-3. Horn Mountain NFB M Sand oil production (MMbbls/year) 2003-2018	8
Exhibit 3-4. Hom Mountain oil field NFB M Sand oil production 2003–2018	
Exhibit 3-5. Hom Mountain oil field NFB M Sand water injection 2003–2011	
Exhibit 3-6. Oil composition, Horn Mountain NFB M Sand	
Exhibit 3-7. Binary interaction coefficients used for the Horn Mountain oil field NFB M	
Sand	. 10
Exhibit 3-8. Relative permeability curves for oil/water and gas/oil, Horn Mountain oil fie	
NFB M Sand	
Exhibit 4-1. Hom Mountain oil field M Sand structure and depth	.11
Exhibit 4-2. Hom Mountain oil field M Sand reservoir model and grid blocks	
Exhibit 4-3. History match of cumulative fluid production, Horn Mountain oil field NFB N	
Sand	
Exhibit 4-4. Comparison of actual and history matched values for oil, gas, and water	
production, Horn Mountain oil field NFB M Sand	. 13
Exhibit 4-5. Reservoir pressure from history match of fluid production, Horn Mountain o	
field NFB M Sand Exhibit 4-6. Oil saturation at end of waterflood, Hom Mountain oil field NFB M Sand	.14
Exhibit 5-1. Horn Mountain oil field NFB M Sand CO2 injection wells and post waterfloo	
oil saturation, scenarios 1–3	
Exhibit 5-2. Horn Mountain oil field NFB M Sand CO2 injection wells and post waterfloo	
oil saturation, scenario 4	
Exhibit 5-3. Horn Mountain oil field NFB M Sand cumulative oil recovery with and without	out
	. 17
Exhibit 5-4. Horn Mountain oil field NFB M Sand cumulative oil recovery with and without	tuc
CO ₂ injection, scenario 4	
Exhibit 5-5. Horn Mountain oil field NFB M Sand CO2 injection wells and post CO2 flood	l oil
saturation, scenarios 1–3.	
Exhibit 5-6. Horn Mountain oil field NFB M Sand CO2 injection wells and post CO2 flood	lio l
saturation, scenario 4	
Exhibit 5-7. Horn Mountain oil field NFB M Sand cumulative CO2 injection and	
production, scenarios 1–3	.21
Exhibit 5-8. Horn Mountain oil field NFB M Sand cumulative CO2 injection and	
production, scenario 4	. 22
Exhibit 5-9. Oil production, CO_2 injection, CO_2 storage, and CO_2 utilization; GEM	
compositional modeling of the CO ₂ flood Hom Mountain oil field NFB M Sand	. 22
Exhibit 6-1. Volumetric and reservoir properties, Horn Mountain oil field total M Sand	
Exhibit 6-2. Volumetric and reservoir properties. Horn Mountain oil field NFB M Sand	

HORN MOUNTAIN OFFSHORE OIL FIELD CASE STUDY

Exhibit 6-3. Input data sheet, CO $_2$ Prophet modeling of Horn Mountain oil field NFB M
Sand (DP = 0.75)26
Exhibit 6-4. Input data sheet, CO ₂ Prophet modeling of Horn Mountain oil field NFB M
Sand (DP = 0.5)27
Exhibit 6-5. Oil production, CO2 injection, and CO2 production; CO2 Prophet modeling
of the CO_2 flood, Horn Mountain oil field NFB M Sand (985 acres, Sor 32.5%, DP = 0.75) 29
Exhibit 6-6. Oil production, CO2 injection, and CO2 production; CO2 Prophet modeling
of the CO_2 flood, Horn Mountain oil field NFB M sand; (985 acres, Sor 32.5%, DP = 0.5)30
Exhibit 7-1. Comparative assessments of performance for the Horn Mountain oil field NFB
M Sand31
Exhibit A-1. Annual Oil Production by Well vs. History Match NFB Horn Mountain
(MMbbl)33
Exhibit A-2. Annual Gas Production by Well vs. History Match NFB Horn Mountain (Bcf)
34
Exhibit A-3. Annual Water Production by Well vs. History Match NFB Horn Mountain
(MMbbl)35
Exhibit B-1. Annual Incremental Oil Production GEM vs. CO2 Prophet (MMbbl)*36
Exhibit B-2. Chart of Annual Incremental Oil Production GEM vs. CO_2 Prophet (MMbbl)
37

ACRONYMS AND ABBREVIATIONS

ф	Reservoir porosity	MESA	Mission Execution and Strategic
Α	Accessible oil area		Analysis
API	American Petroleum Institute	mi	Mile
ARI	Advanced Resources	MM	Million
	International	MMbbl(s)	Million barrels
atm	Atmosphere	MMcfd	Millions of cubic feet per day
Ave Pres Po	OVO SCTR Average pressure for	MW	Molecular weight
	pore volume per sector	NETL	National Energy Technology
B/AF	Barrels per acre foot		Laboratory
bbl	Barrel	NFB	North Fault Block
bbl/d	Barrel per day	OCS	Outer Continental Shelf
Bcf	Billion cubic feet	OOIP	Original oil in place
Воі	Initial oil formation volume	Рс	Critical pressure
	factor	psi	Pounds per square inch
CFB	Central Fault Block	psia	Pound per square inch
cfd	Cubic feet per day		absolute
CO_2	Carbon dioxide	SC	Standard conditions
Cum	Cumulative	scf	Standard cubic foot
DOE	Department of Energy	Sg	gas saturation
DP	Dykstra-Parsons	Sim	Simulated
EFB	East Fault Block	Soi	Initial oil saturation
EOR	Enhanced oil recovery	Sor	Residual oil saturation
F	Netpay	Sw	Water saturation
ft	Foot	Swi	Initial water saturation
GOM	Gulf of Mexico	Tc	Critical temperature
K	Kelvin	TVDSS	True vertical depth below sea
Kr	Relative permeability		surface
Krg	Gas relative permeability	U.S.	United States
Krog	Oil relative permeability for	°F	Degrees Fahrenheit
	gas-oil system		
Krow	Oil relative permeability for		
	water-oil system		
Krw	Water relative permeability		
Mcf	Thousand cubic feet		
mD	Millidarcy		

1 Introduction

Offshore Gulf of Mexico (GOM) outer continental shelf (OCS) oil fields offer significant potential for storage of carbon dioxide (CO₂) emissions and incremental production of oil using CO₂ enhanced oil recovery (EOR). The National Energy Technology Laboratory (NETL) has developed a robust set of onshore CO₂ EOR modeling tools (e.g., the Fossil Energy/NETL CO₂ Prophet Model [CO₂ Prophet Model]), [1] [2] which may be adaptable for modeling offshore CO₂ EOR potential. However, rigorous evaluation of CO₂ storage and CO2 EOR in the offshore also requires information on offshore reservoir characteristics, existing oil field infrastructure, and other key features.

A subset of GOM OCS offshore oil fields were investigated to identify three case studies -- Horn Mountain oil field (discussed in this report), Cognac oil field, [3] and Petronius oil field [4] –that would help generate an initial body of knowledge on the challenges of evaluating the potential of offshore CO₂ EOR and CO₂ storage. A primary purpose of these case studies was to assess to what extent the CO₂ Prophet Model can reasonably represent the performance of an offshore CO₂ flood, including capturing the geologic complexity and irregular well spacings typical of offshore oil fields. To perform the assessment of the capabilities of the CO₂ Prophet Model, the following seven tasks were completed:

- 1. Built a representative geologic model for the Horn Mountain oil North Fault Block (NFB) M Sand including capturing its structural setting and associated aquifer
- 2. Assembled the key reservoir properties of the NFB M Sand, including its volumetric data, fluid flow capabilities (including relative permeability curves), and oil composition to construct a reservoir model
- 3. Established the locations of the existing oil/gas production wells and water injection wells in the NFB M Sand
- 4. Used Computer Modelling Group Ltd.'s GEM compositional simulator ("GEM") to provide a "first-order" history match of fluid production from the NFB M Sand and to calibrate the NFB M Sand's geologic and reservoir description with its oil, gas, and water production history
- 5. Appraised the performance of a post-waterflood CO₂ EOR project in the NFB M Sand using GEM with a calibrated geologic/reservoir description
- 6. Appraised the performance of a post-waterflood CO₂ EOR project in the NFB M Sand using the CO₂ Prophet Model (a variant of the NETL CO₂ Prophet Model with similar functionality and performance analysis) in parallel with GEM
- 7. Compared the modeling results of a post-waterflood CO₂ EOR project in the Horn Mountain oil field NFB M Sand from GEM and the CO₂ Prophet Model to determine whether the CO₂ Prophet Model could reasonably represent the performance of the CO₂ flood compared to the more sophisticated GEM

2 HORN MOUNTAIN OIL FIELD

The Horn Mountain oil field (MC126/MC127) is located in Central GOM, approximately 80 miles from onshore Louisiana (Exhibit 2-1). [5] Horn Mountain, while located in 4,500 feet of water depth, has a structurally complex reservoir setting, analogous to shallow water Central GOM oil fields. As such, this field provides a representative geologic setting for appraising the potential of conducting CO₂ EOR in both shallow and deep-water oil fields. Horn Mountain oil field, with 138 million (MM) barrels (bbl) of original oil reserves and 127 billion cubic feet (Bcf) of original gas reserves, has produced over 85 percent of its original oil and gas reserves, as of the end of 2017. Oil production, that peaked at over 58,000 bbl per day (bbl/d) in 2003, has declined to 12,500 bbl/d in 2018. This implies that Horn Mountain oil field will be depleted within five to ten years, making it a priority candidate for EOR using injection of CO₂.




Exhibit 2-1. Location of Horn Mountain oil field, Central GOM

Horn Mountain oil field was developed using a free-floating truss spar, the largest of its kind in the world at the time, measuring 580 feet (ft) high and 110 ft in diameter, with space for 14 wells. After appraisal drilling, eight production wells and two water injection wells were drilled in 2001–2003. With concerns about the strength of the aquifer underlying the oil field, the operator initiated a waterflood in 2003 that lasted until 2011.

As part of an initial review of the potential of offshore CO₂ EOR, Exhibit 2-2 illustrates how a regional offshore CO₂ pipeline system could connect the Horn Mountain oil field and other offshore oil fields to CO₂ supplies from onshore Alabama and Mississippi. [5]




Exhibit 2-2. Potential CO₂ pipeline system for Horn Mountain oil field, Central GOM

2.1 STRUCTURAL SETTING

The Horn Mountain oil field includes two stacked Middle Miocene sands (reservoirs)-- the J Sand and the M Sand. The reservoirs dip to the southwest and are bounded by several large structural faults. These faults divide the field into three distinct production areas-- North Fault Block (NFB), Central Fault Block (CFB), and East Fault Block (EFB) (Exhibit 2-3).




Exhibit 2-3. Horn Mountain M Sand well locations, structural features, and fault blocks

AAPG©2007, reprinted by permission of the AAPG whose permission is required for further use [6]

The northwest to southeast cross-section for Horn Mountain shows the oil bearing (green) portions of the J Sand and the M Sand, separated by a thin gas bearing (red) K Sand (Exhibit 2-4, data from Milkov [6]). The M Sand is layered with internal shale sequences (gray), particularly in the CFB and EFB. In the NFB, the M Sand is a relatively uniform anticlinal structure with bounding faults on the north and east.




Exhibit 2-4. Horn Mountain J Sand and M Sand and well locations

2.2 HORN MOUNTAIN OIL RESOURCES

The M Sand, the largest sand in the Horn Mountain oil field, has 367 MMbbls of original oil in place (OOIP) and an expected recovery efficiency of about 33 percent (after waterflooding) making it an attractive candidate for CO₂ EOR, (Exhibit 2-5). [5] The J Sand has OOIP of 40 MMbbls and is too small for a stand-alone EOR project. However, joint development with the M Sand could enable the J Sand to also be included in a CO₂ EOR project.

Exhibit 2-5. Horn Mountain oil resources, cumulative production, and remaining reserves

Sands	Oil Area (Acres)	OOIP (MMbbls)	Cumulative Oil Production ^A (MMbbls)	Remaining Oil Reserves ^A (MMbbls)
Major Sands				
M	5,800	367	106.2	15.2
Minor Sands				
J	690	40	11.4	2.9
N-Lower	80	4	0	1.8
Total	6,570	411	117.6	19.9

AAs of end of 2017

Source: Bureau of Ocean Energy Management (BOEM) data, 2018

3 HORN MOUNTAIN NFB M SAND

The reservoir modeling addresses the M Sand in the NFB of Horn Mountain oil field, as identified by the yellow outline in Exhibit 3-1. The M sand in NFB has been developed with three production wells (A4, A3, and A2) and one water injection well (A6). As of the end of 2018, the three production wells are still active; however, water injection well A6 is currently inactive. Exhibit 3-2 provides the key volumetric and reservoir properties for the Horn Mountain NFB M Sand.




Exhibit 3-1. Horn Mountain NFB M Sand oil production and water injection wells

AAPG @ 2007, reprinted by permission of the AAPG whose permission is required for further use $\[6]$

Exhibit 3-2. Reservoir properties, Horn Mountain NFB M Sand

Property	Value
Accessible Oil Area (acres)	985
Porosity (%)	27
Permeability Horizontal (mD)	250
Permeability Vertical (mD)	25
Permeability Anisotropy	15 to 1
Net Pay (ft)	132
Oil Gravity (°API)	32
Swi	0.22
Soi	0.78
Boi (rb/stb)	1.38
OOIP (MMbbls)	154
Gas/Oil Ratio (scf/bbl)	803
Initial Pressure (at 14,250 ft) (psia)	7,675
Initial Reservoir Temperature (°F)	200

Based on the reservoir properties in Exhibit 3-2, the OOIP for the NFB M Sand is 154 MMbbls, as calculated below:

In the OOIP equation above, A is the accessible oil area, F is the average payzone net thickness, Soi is the initial oil saturation, and ϕ is reservoir porosity. Oil production from the NFB M Sand reached a peak of 24,900 bbl/d in 2004 and declined steadily until 2011, with a brief uptick in production between 2012 and 2014. After 2014, oil production resumed its decline to a current (2018) rate of 4,010 bbl/d. Exhibit 3-3 illustrates the oil production history for the three production wells in the Horn Mountain NFB M Sand. As of the end of 2018, the Horn Mountain NFB M Sand had produced 64.7 MMbbls of oil. [7]




Exhibit 3-3. Horn Mountain NFB M Sand oil production (MMbbls/year) 2003–2018

Exhibit 3-4 provides tabular data on the annual oil production history for the three Horn Mountain NFB M Sand oil production wells.

Exhibit 3-4. Horn Mountain oil field NFB M Sand oil production 2003–2018

Year	Well A004	Well A003	Well A002	Total (MMbbls)
2003	3.1	2.6	3.1	8.7
2004	3.0	3.5	2.5	9.1
2005	2.5	2.8	2.1	7.4
2006	2.4	2.7	2.3	7.3
2007	2.0	1.4	2.1	5.5
2008	1.7	0.7	2.3	4.6
2009	1.5	0.6	1.9	4.0
2010	1.4	0.2	1.3	2.9
2011	0.9	0.3	0.6	1.8
2012	1.0	0.2	0.7	1.9
2013	1.1	0.0	1.1	2.2
2014	1.2	0.1	1.0	2.3
2015	1.0	0.1	0.8	1.9
2016	1.0	0.0	0.8	1.8
2017	0.9	0.0	0.7	1.6
2018	0.9	0.0	0.6	1.5
Total	25.7	15.1	23.9	64.7

Exhibit 3-5 provides a summary of water injection data from 2003 to 2011 for the waterflood in the Horn Mountain oil field NFB M Sand. A total of 6.1 MMbbls of water was injected over eight years. [7]




Exhibit 3-5. Horn Mountain oil field NFB M Sand water injection 2003–2011

Exhibit 3-6 and Exhibit 3-7 provide the hydrocarbon composition and binary interaction coefficients for the 32° American Petroleum Institute (API) gravity oil in the Horn Mountain oil field NFB M sand with a gas/oil ratio of 803 standard cubic feet (scf)/bbl. The oil composition used for the GEM model was based on data from Li et al. (2017) for a Wolfcamp reservoir oil with similar API gravity and reservoir characteristics [8]

Component Composition (%) CO_2 0.35 N_2 1.16 C1 35.32 C2 8.66 C3 8.55 iC4 1.06 C4 4.86 C5-C6 7.66 15.70 C7-C12 C13-C21 8.50 C22+ 8.23

Exhibit 3-6. Oil composition, Horn Mountain NFB M Sand


Exhibit 3-7. Binary interaction coefficients used for the Horn Mountain oil field NFB M Sand


Commonant	Pc	Tc	MW		Binary Interaction Coefficients						
Component	(atm)	(K)	IVIVV	CO ₂	N ₂	C1	C2	С3	IC4	NC4	C5-C6
CO ₂	72.8	304.2	44.01	0							
N ₂	33.5	126.2	28.01	0	0						
C1	45.4	190.6	16.04	0.105	0.025	0					
C2	48.2	305.4	30.07	0.13	0.01	0.0027	0				
С3	41.9	369.8	44.09	0.125	0.09	0.0085	0.0017	0			
IC4	36	408.1	58.12	0.12	0.095	0.0157	0.0055	0.0011	0		
NC4	37.5	425.2	58.12	0.115	0.095	0.0147	0.0049	0.0009	0.0000	0	
C5-6	31.4	486.4	78.3	0.115	0.1	0.0319	0.0165	0.0077	0.0030	0.0035	0
C7-12	24.7	585.1	120.6	0.115	0.11	0.0470	0.0279	0.0162	0.0089	0.0097	0.0016
C13-21	17.0	740.1	220.7	0.115	0.11	0.1003	0.0728	0.0539	0.0402	0.0417	0.0218
C22-80	12.9	1024	443.5	0.115	0.11	0.1266	0.0964	0.0750	0.0590	0.0608	0.0365

Source: Modified from Li, 2017. [8]

Exhibit 3-8 provides the relative permeability curves for oil/water and gas/oil based on history matching Horn Mountain NFB M Sand fluid production.

Exhibit 3-8. Relative permeability curves for oil/water and gas/oil, Horn Mountain oil field NFB M Sand





4 RESERVOIR MODEL FOR THE HORN MOUNTAIN OIL FIELD NFB M SAND

This section describes the construction and calibration of the reservoir model for the Horn Mountain oil field NFB M Sand. Also, this section discusses calibration of the reservoir model.

4.1 Constructing the Reservoir Model

Exhibit 4-1 illustrates the structure and depth of the Horn Mountain NFB M Sand as well as the location of the three oil production wells (A4, A3, and A2) and the location of the water injection well (A6). A northeast to southwest 7-degree dip was implemented, based on reported wellbore locations. The structure around production well A2 is very complex, so A2 elevation in the model is approximate. [7]




Exhibit 4-1. Horn Mountain oil field M Sand structure and depth

Exhibit 4-2 shows the reservoir model's grid blocks for the Horn Mountain oil field NFB M Sand and its associated aquifer. The model area is defined by 43 x-direction and 35 y-direction grid blocks. With each grid block representing 200 square feet, the total model area encompasses 1,380 acres. A fault along the northern portion of the fault block reduces the productive area of the NFB M Sand to 985 acres.

The model contains six vertical grid blocks, each 22 ft thick, to provide higher resolution and to model gravity effects on injected and produced fluids. The bottom grid block represents the oilwater contact at 14,300 feet reservoir depth. The light blue portion of Exhibit 4-2 represents the area on the north of the NFB area, separated from the oil-bearing M Sand by a major fault. [7]




Exhibit 4-2. Horn Mountain oil field M Sand reservoir model and grid blocks

4.2 CALIBRATING THE RESERVOIR MODEL

To calibrate the Horn Mountain oil field, the study assembled a data set representative of the Horn Mountain NFB M Sand to perform a "first-order" history match of the oil, gas, and water production reported for the M Sand for the period 2003 through 2018. (Actual pressure data were not available in the BOEM data set or in the technical literature.) Reported fluid production values were closely matched with the GEM compositional simulator, using the M Sand structure, its reservoir properties, and other parameters, as shown in Exhibit 4-3 [7] and Exhibit 4-4. [7]

For the history match, the oil production rate in GEM was constrained to match the actual production rate observed from the three production wells in the NFB M Sand. Since gas is in solution, gas production was controlled using the gas/oil ratio observed in the field. An aquifer was implemented in the model to match water production. In addition, 6 MMbbls of water were injected during the waterflood, and a total of 24 MMbbls of water were produced in the history match consistent with actual water injection and production data. Additional data and information on well by well production from the "first-order" history match are provided in Appendix A.

 $\textbf{Exhibit 4-3. History match of cumulative fluid production, Horn Mountain oil field NFB\,M\,S and}$




Exhibit 4-4. Comparison of actual and history matched values for oil, gas, and water production, Horn Mountain oil field NFB M Sand

Fluid	Actual Data	History Matched Data
Oil (MMbbls)	64.7	64.7
Gas (Bcf)	51	52
Water (MMbbls)	24.8	24.3

An important output of the history match was the estimate of NFB M Sand reservoir pressure at the end of primary production (Exhibit 4-5) providing important information for designing CO₂ injectivity and volumes for the proposed miscible CO₂ flood in the M Sand.




Exhibit 4-5. Reservoir pressure from history match of fluid production, Horn Mountain oil field NFB M Sand

A most important outcome of the history matching step was establishing the location of the oil saturations remaining in the Horn Mountain oil field NFB M Sand reservoir at the end of the waterflood (Exhibit 4-6). [7] This information helped establish the optimum locations for placing the new CO₂ injection wells in the proposed CO₂ flood.




Exhibit 4-6. Oil saturation at end of waterflood, Horn Mountain oil field NFB M Sand

5 GEM MODELING THE PERFORMANCE OF THE CO₂ FLOOD, HORN MOUNTAIN OIL FIELD NFB M SAND


The reservoir model constructed for the Horn Mountain oil field NFB M Sand (Section 4) was placed into the GEM reservoir simulator to evaluate the expected performance of the CO₂ flood.

5.1 CO₂ FLOOD DESIGN

To optimize the CO_2 flood in the NFB M Sand, this case study set forth three CO_2 injection scenarios. Each scenario represents a different set of CO_2 injection well placements targeting areas of the reservoir with high remaining oil saturations (Exhibit 5-1):

- Each of the three CO₂ flooding scenarios drilled two new up dip CO₂ injection wells between the existing oil production wells and the fault in the northwest portion of the NFB and converted the existing water injection well (A6) to a CO₂ injection well
- Each scenario injected continuous CO₂ at a rate of 72 MM cubic feet per day (cfd) (24 MMcfd for three injection wells) into the NFB M Sand for 20 years, using a maximum bottom hole pressure of 9,000 psi
- Each scenario used a line drive pattern, with a 1:1 injector-to-producer ratio, for the CO₂ flood design

Exhibit 5-1. Horn Mountain oil field NFB M Sand CO_2 injection wells and post waterflood oil saturation, scenarios 1-3



In addition to the three scenarios discussed above, the study examined a more capital-intensive fourth scenario involving drilling three new CO₂ injection wells and shutting in the currently inactive A6 water injection well (Exhibit 5-2).





Exhibit 5-2. Horn Mountain oil field NFB M Sand CO₂ injection wells and post waterflood oil saturation, scenario 4

5.2 CALCULATED OIL RECOVERY


GEM modeling of the CO₂ flood in the Horn Mountain oil field NFB M Sand provided the following volumes of incremental oil recovery (beyond primary and waterflood) following 20 years of CO₂ injection (Exhibit 5-3).


- Scenario 1 19.2 MMbbl of incremental oil recovery, equal to 12.5 percent of OOIP
- Scenario 2 15.5 MMbbl of incremental oil recovery, equal to 10.1 percent of OOIP
- Scenario 3 22.5 MMbbl of incremental oil recovery, equal to 14.6 percent of OOIP

Exhibit 5-3. Horn Mountain oil field NFB M Sand cumulative oil recovery with and without CO $_2$ injection, scenarios 1-3



The more capital-intensive Scenario 4 CO_2 flood achieved 29.0 MMbbls of oil recovery, equal to 18.8 percent of OOIP (Exhibit 5-4).





A review of the performance of the three main CO_2 flooding scenarios shows that Scenario 3 achieved the highest contact with the NFB M sand, while leaving behind the lowest residual oil saturation (Exhibit 5-5).




Exhibit 5-5. Horn Mountain oil field NFB M Sand CO_2 injection wells and post CO_2 flood oil saturation, scenarios 1-3

By drilling three new up dip CO_2 injection wells, Scenario 4 contacted more of the residual oil saturation of the M Sand in NFB, enabling this more costly and sophisticated CO_2 EOR flood to maximize oil recovery (Exhibit 5-6).




Exhibit 5-6. Horn Mountain oil field NFB M Sand CO2 injection wells and post CO2 flood oil saturation, scenario 4

5.3 CALCULATED CO₂ INJECTION, PRODUCTION, AND STORAGE

GEM modeling of the CO_2 flood in the Horn Mountain oil field NFB M Sand also provided the following data on CO_2 production and storage for the 20-year CO_2 flood (Exhibit 5-7). Each scenario used gross CO_2 injection of 526 Bcf into three CO_2 injection wells.

- Scenario 1 Production and recycling of 255 Bcf for total storage of 271 Bcf
- Scenario 2 Production and recycling of 268 Bcf for total storage of 258 Bcf
- Scenario 3 Production and recycling of 264 Bcf for total storage of 262 Bcf




Exhibit 5-7. Horn Mountain oil field NFB M Sand cumulative CO₂ injection and production, scenarios 1−3

With increased reservoir contact and higher oil recovery, Scenario 4 is also able to provide notably higher volumes of CO₂ storage (Exhibit 5-8).




Exhibit 5-8. Horn Mountain oil field NFB M Sand cumulative CO2 injection and production, scenario 4

Exhibit 5-9 provides the cumulative data for oil production, the cumulative data for CO_2 injection and storage, and the gross and net CO_2 utilization for CO_2 EOR for scenarios 1–3 in the Horn Mountain oil field NFB M Sand. For the 20-year CO_2 flood, gross CO_2 utilization is between 23.4 thousand cubic feet (Mcf)/bbl and 33.9 Mcf/bbl. Net CO_2 utilization is between 11.6 Mcf/bbl and 16.6 Mcf/bbl, equal to 0.61 to 0.88 metric tons of CO_2 stored per bbl of oil recovered.

Exhibit 5-9. Oil production, CO_2 injection, CO_2 storage, and CO_2 utilization; GEM compositional modeling of the CO_2 flood Horn Mountain oil field NFB M Sand

	Incremental Oil Production	Cumula	ntive CO ₂	CO ₂ Utilization		
Scenario	Cumulative (MMbbls)	Injection (Bcf)	Storage (Bcf)	Gross (Mcf/bbl)	Net (Mcf/bbl)	
1	19.2	526	271	27.4	14.1	
2	15.5	526	258	33.9	16.6	
3	22.5	526	262	23.4	11.6	

The Scenario $4 \, \text{CO}_2$ flood, involving additional well drilling and capital investment, provided higher values for oil recovery and CO_2 storage—29.0 MMbbls for oil recovery and 350 Bcf for CO_2 storage—than achieved by scenarios 1, 2, or 3 CO_2 floods. An economic assessment, not performed by this case study, would be required to establish under what oil price outlooks the extra capital expenditures incurred by Scenario 4 would be justified by the higher volumes of oil recovery and CO_2 storage.

6 MODELING THE PERFORMANCE OF THE HORN MOUNTAIN OIL FIELD NFB M SAND CO₂ FLOOD WITH CO₂ PROPHET MODEL

In parallel with GEM, the CO₂ Prophet Model was used to evaluate the expected performance of the CO₂ flood in the Horn Mountain oil field NFB M Sand using the volumetric and reservoir properties data established in Section 3. Exhibit 6-1 provides the volumetric and reservoir property data for the Horn Mountain oil field total M Sand. Exhibit 6-2 provides the key volumetric and reservoir property data for modeling the Horn Mountain oil field NFB M Sand. Exhibit 6-3 and Exhibit 6-4 are the input data sheets for modeling the CO₂ flood in the Horn Mountain oil field M Sand using the CO₂ Prophet Model.

To capture the heterogeneity of the M Sand, a Dykstra-Parsons (DP) coefficient of 0.75 was first used in CO_2 Prophet modeling. The impact of using a more favorable DP coefficient of 0.5, that would represent a considerably more uniform reservoir sand, was also examined.^a

6.1 Use of Dykstra-Parsons (DP) to Capture Features Not Available in the CO2 Prophet Model

Because CO_2 Prophet does not handle gravity override or reservoir heterogeneity in a CO_2 flood (important features that are captured by the GEM Model), we use the DP function to represent these features. The DP function in CO_2 Prophet places the higher perm layers at the top of the reservoir, partially capturing the effects of gravity override by the CO_2 . A higher DP value in CO_2 Prophet can also be used to capture the effects of reservoir heterogeneity due to anisotropy and other reasons. In general, a DP value of 0.5 represents a favorable, relatively thin offshore reservoir. A value of 0.75 is commonly used to represent a favorable but thicker and more heterogeneous, onshore reservoir.

With no means of directly modeling anisotropy or CO₂ override in CO₂ Prophet, the DP value is the best "control knob" that the study has for approximating the effects of these features on reservoir performance. We bracketed the results with two DPs to show a range of outcomes relative to the GEM model results.

23

^a The DP coefficient is used by the reservoir engineering community to define the heterogeneity of a reservoir, with a low value (0.5 or so) reflecting low heterogeneity and a high value (0.9 or so) reflecting high heterogeneity. A full-scale, compositional reservoir model typically assigns different permeability values to discrete units of net pay (the vertical stack of grid blocks) to capture the reservoir heterogeneity.

Exhibit 6-1. Volumetric and reservoir properties, Horn Mountain oil field total M Sand

Basin Name	FED-OFF		Area:	Offshore		^
State	LA		, , , , , , , , , , , , , , , , , , , ,	To change Basin, click on cell above		
Field Name	MC084 - Horn Moun	tain	Reservoir Number	23469		
			Manual	23469		~
Reservoir	M Sand		Total Reservoirs	595		
			•			
Reservoir Parameters:		Oil Production		Volumes	_	
Area (A)	5,803	Producing Wells (active)	7	OOIP (MMbI)	103	366.9
Net Pay (ft)	57	Producing Wells (shut-in)	0	Cum P/S Oil (MMbl)	L	106.2
Depth (ft)	14,250	2018 Production (MMbbl)	2.16	EOY 2018 P/S Reserves (MMbI)	L	15.2
Lithology	1	2018 P/S Production (MMbbl)	2.16	Ultimate P/S Recovery (MMbl)	L	121.4
Dip (°)	0	Cum Oil Production (MMbbl)	106.2	Remaining (MMbbl)		245.5
Gas/Oil Ratio (Mcf/Bbl)	803	EOY 2018 Oil Reserves (MMbbl	15.2	Ultimate P/S Recovered (%)	L	33%
Salinity (ppm)	98,376	Water Cut	65.7%	P/S Sweep Efficiency (%)	106	63%
Gas specific Gravity	0.62			OOIP Volume Check	_	
Historical Well Spacing (Acres)	-1	Water Production		Reservoir Volume (AF)	L	333,116
Current Pattern Acreage (Acres)	160	2018 Water Production (Mbbl)	4.1	Bbl/AF	L	1,101.4
Permiability (mD)	250	Daily Water (Mbbl/d)	0.0	OOIP Check (MMbI)		366.9
Porosity (%)	24%					
Reservoir Temp (deg F)	203	Injection		SROIP Volume Check	(
Initial Pressure (psi)	7675	Injection Wells (active)	2	Reservoir Volume (AF)		333,116
Pressure (psi)	-1	Injection Wells (shut-in)	0	Swept Zone Bbl/AF		527
		2018 Water Injection (MMbbl)	0	SROIP Check (MMbbl)		175.5
Boi	1.32	Daily Injection - Field (Mbbl/d)	0.00			
B _o @ S _o , swept	1.15	Cum Injection (MMbbl)	0.0			
Soi	0.78	Daily Inj per Well (Bbl/d)	0.0	ROIP Volume Check		
Sor	0.325			ROIP Check (MMbl)		245.5
S _{wi}	0.22	EOR				
S _w	0.675	Туре	0			
-		2018 EOR Production (MMbbl)	0.0			
API Gravity	32.0	Cum EOR Production (MM bbl)	0.0			
Viscosity (cp)	0.69	EOR 2018 Reserves (MMbbl)	0.0			
, (,		Ultimate Recoverery (MMbbl)	0.0			
Dykstra-Parsons	0.85	OGJ Data				
Miscibility:		2018 Enhanced Production (B/d	0			
C5+ Oil Composition	208.1	2018 Total Production (B/d)	0			
Min Required Miscibility Press(psig)	2825.4	Project Acreage	0			
Depth > 3000 feet	1	Scope	0			
API Gravity >= 17.5	1	# Projects	0			
Pr > MMP	0	,				

Flood Type

Miscible

Exhibit 6-2. Volumetric and reservoir properties, Horn Mountain oil field NFB M Sand

Basin Name	FED-OFF		Area:	Offshore		^
State	LA		_	To change Basin, click on cell above		
Field Name	MC084 - Horn Moun	tain	Reservoir Number	23469		
			Manual	23469		~
Reservoir	NFB M Sand		Total Reservoirs	595		
Reservoir Parameters:		Oil Production		Volumes		
Area (A)	985	Producing Wells (active)	3	OOIP (MMbI)	103	153.9
Net Pay (ft)	132	Producing Wells (shut-in)	0	Cum P/S Oil (MMbl)		64.7
Depth (ft)	14,250	2018 Production (MMbbl)	1.46	EOY 2018 P/S Reserves (MMbI)		10.3
ithology	1	2018 P/S Production (MMbbl)	1.460	Ultimate P/S Recovery (MMbl)		75.0
Dip (*)	0	Cum Oil Production (MMbbl)	64.7	Remaining (MMbbI)		79.0
Gas/Oil Ratio (Mcf/Bbl)	803	EOY 2018 Oil Reserves (MMbbl	10.3	Ultimate P/S Recovered (%)		49%
Salinity (ppm)	98,376	Water Cut	58.5%	P/S Sweep Efficiency (%)	106	97%
Gas specific Gravity	0.62			OOIP Volume Check		
Historical Well Spacing (Acres)	-1	Water Production		Reservoir Volume (AF)		130,026
Current Pattern Acreage (Acres)	160	2018 Water Production (Mbbl)	2.1	Bbl/AF		1,183.9
Permiability (mD)	250	Daily Water (Mbbl/d)	0.01	OOIP Check (MMbI)		153.9
Porosity (%)	27%					
Reservoir Temp (deg F)	203	Injection		SROIP Volume Check		
nitial Pressure (psi)	7675	Injection Wells (active)	1	Reservoir Volume (AF)		130,026
Pressure (psi)	-1	Injection Wells (shut-in)	0	Swept Zone Bbl/AF		592
		2018 Water Injection (MMbbl)	0	SROIP Check (MMbbl)		77.0
B _{oi}	1.38	Daily Injection - Field (Mbbl/d)	0.00			
B。@ S。 swept	1.15	Cum Injection (MMbbl)	0.0			
Soi	0.78	Daily Inj per Well (Bbl/d)	0.0	ROIP Volume Check		
S _{or}	0.325			ROIP Check (MMbl)		79.0
S _{wi}	0.22	EOR			_	
S _w	0.675	Туре	0			
		2018 EOR Production (MMbbl)	0.0			
API Gravity	32.0	Cum EOR Production (MMbbl)	0.0			
Viscosity (cp)	0.69	EOR 2018 Reserves (MMbbl)	0.0			
(-1)		Ultimate Recoverery (MMbbl)	0.0			
Dykstra-Parsons	0.75	OGJ Data				
Miscibility:		2018 Enhanced Production (B/d	0			
C5+ Oil Composition	208.1	2018 Total Production (B/d)	0			
Min Required Miscibility Press(psig)	2825.4	Project Acreage	0			
Depth > 3000 feet	1	Scope	0			
API Gravity >= 17.5	1	# Projects	0			
Pr > MMP	0	-				

Flood Type

Miscible

Exhibit 6-3. Input data sheet, CO₂ Prophet modeling of Horn Mountain oil field NFB M Sand (DP = 0.75)

'Horn Mountain NFB 985 ac Base Case Line Drive DP 75'							
*********	WELL AND PATTE	RN DATA *****	**'				
'PATTERN'							
'LD'							
'NWELLS	NOINJ'						
2,	1						
'WELLS	WELLY	WELLO'					
0,	0,	1					
1,	1,	-1					
'NBNDPT'							
5							
'BOUNDX	BOUNDY'						
0,	0						
0,	1						
1,	1						
1,	0						
-	0						
0,	-	TD015					
	* PROGRAM CON	IKULS ******	•				
'LWGEN	OUTTIM'						
'N',	1						
'**** RELATIV	E PERMEABILITY	PARAMETERS **	* *				
'SORW	SORG	SORM'					
0.20,	0.3,	0.1					
'SGR	SSR'						
0.3,	0.3						
'SWC							
	SWIR'						
0.3,	0.3						
'KROCW	KWRO	KRSMAX	KRGCW'				
0.8,	0.2,	0.4,	0.45				
'EXPOW	EXPW	EXPS	EXPG	EXPOG'			
2,	2,	2,	2,	2			
'KRMSEL	W'	-	-				
1,	0.999						
·*********	*** FLUID DAT	Δ ********	* *				
'VISO		CO2SOL Ø REDF		1			
	0.38	COZSOL & KLDI	AC 0.10 CO21N	3			
0.69,		4.0.7	5414				
'BO	RS	API	SALN	GSG'			
1.15,	804,	32,	98375,	0.62			
	** RESERVOIR D		* '				
'TRES	P	MMP'					
203,	9000,	2825					
'DPCOEF	PERMAV	THICK	POROS	NLAYERS'			
0.50,	250,	132,	0.27,	10			
'SOINIT	SGINIT	SWINIT'	- · - · ,				
0.325,	0,	0.675					
'AREA	XKVH'	0.075					
42906600,	1						
	NJECTION PARAM	EIERS ******	* '				
'NTIMES	WAGTAG'						
1,	'T'						
'HCPVI	WTRRAT	SOLRAT	TMORVL'				
1.04,	27000,	72,	0.0				
_	•	•					

Exhibit 6-4. Input data sheet, CO_2 Prophet modeling of Horn Mountain oil field NFB M Sand (DP = 0.5)

'Horn Mountain NFB 985 ac Base Case Line Drive DP 50'						
**********	WELL AND PATTE	RN DATA *****	**			
'PATTERN'						
'LD'						
'NWELLS	NOINJ'					
2,	1					
'WELLS	WELLY	WELLQ'				
0,	0,	1				
1,	1,	-1				
'NBNDPT'						
5						
'BOUNDX	BOUNDY'					
0,	0					
0,	1					
1,	1					
1,	0					
0,	0					
	** PROGRAM CON	TROLS ******	81			
'LWGEN	OUTTIM'					
'N',	1					
	E PERMEABILITY		*'			
'SORW	SORG	SORM'				
0.20,	0.3,	0.1				
'SGR	SSR'					
0.3,	0.3					
'SWC	SWIR'					
0.3,	0.3					
'KROCW	KWRO	KRSMAX	KRGCW'			
0.8,	0.2,	0.4,	0.45			
'EXPOW	EXPW	EXPS	EXPG	EXPOG'		
2,	2,	2,	2,	2		
'KRMSEL	W"					
1,	0.999					
	**** FLUID DAT	A *********	*'			
'VISO	VISW'	CO2SOL 0 REDF	AC 0.10 CO2IN	IJ		
0.69,	0.38					
'BO	RS	API	SALN	GSG'		
1.15,	804,	32,	98375,	0.62		
	*** RESERVOIR D		81			
'TRES	P	MMP '				
203,	9000,	2825				
'DPCOEF	PERMAV	THICK	POROS	NLAYERS'		
0.50,	250,	132,	0.27,	10		
'SOINIT	SGINIT	SWINIT'				
0.325,	0,	0.675				
'AREA	XKVH'					
42906600,	1					
	INJECTION PARAM	ETERS ******	81			
'NTIMES	WAGTAG'					
1,	'T'					
'HCPVI	WTRRAT	SOLRAT	TMORVL'			
1.04,	27000,	72,	0.0			

6.2 CO₂ FLOOD DESIGN

The structural setting and well locations of the Horn Mountain oil field NFB M Sand were modeled with the CO₂ Prophet Model using the following features:

- Drill two new CO₂ injectors and convert the A6 water injection well into a CO₂ injector;
 operate the CO₂ flood using a line drive spacing pattern
- Inject continuous CO₂ at a rate of 72 MMcfd for 20 years, reaching a cumulative injection of CO₂ of 528 Bcf, equal to the CO₂ injected in GEM (hydrocarbon pore volume of 1.0).

6.3 CALCULATED OIL RECOVERY

 CO_2 Prophet modeling of the CO_2 flood in the Horn Mountain oil field NFB M Sand with a DP coefficient of 0.75 provided incremental oil recovery (beyond the waterflood) of 16.1 MMbbls. CO_2 Prophet modeling of the CO_2 flood in the Horn Mountain oil field NFB M Sand with a DP coefficient of 0.5 provided incremental oil recovery (beyond the waterflood) of 23.4 MMbbls.

6.4 CO₂ INJECTION, PRODUCTION, AND STORAGE

CO₂ Prophet modeling of the CO₂ flood in the Horn Mountain oil field NFB M Sand provided the following data for CO₂ injection, CO₂ production, and CO₂ storage for a 20-year CO₂ flood.

- For the DP = 0.75 case, CO₂ injection of 528 Bcf, CO₂ production of 312 Bcf, and CO₂ storage of 215 Bcf for a 20-year CO₂ flood, with CO₂ to oil ratios of 32.8 Mcf/bbl (gross) and 13.4 Mcf/bbl (net)
- For the DP = 0.5 case, CO₂ injection of 528 Bcf, CO₂ production of 245 Bcf, and CO₂ storage of 283 Bcf for a 20-year CO₂ flood, with CO₂ to oil ratios 22.6 Mcf/bbl (gross) and 12.1 Mcf/bbl (net)

Exhibit 6-5 (for DP = 0.75) and Exhibit 6-6 (for DP = 0.5) provide the data for oil production, CO_2 injection and CO_2 production for the CO_2 flood in the Horn Mountain oil field NFB M Sand using the CO_2 Prophet Model.

Exhibit 6-5. Oil production, CO_2 injection, and CO_2 production; CO_2 Prophet modeling of the CO_2 flood, Horn Mountain oil field NFB M Sand (985 acres, Sor 32.5%, DP = 0.75)

Year	CO₂ Inj (Bcf)	Oil Prod (MMbbls)	CO₂ Prod (Bcf)	Purch CO ₂ (Bcf)	CO₂ Util (Mcf/bbl)
1	26.3	1.3	0.0	26.3	20.4
2	52.6	3.0	3.8	48.8	16.0
3	78.9	4.5	13.0	65.9	14.8
4	105.2	5.6	24.9	80.3	14.3
5	131.5	6.7	38.4	93.1	13.9
6	157.8	7.7	52.9	104.9	13.6
7	184.1	8.6	68.5	115.6	13.4
8	210.4	9.4	85.1	125.3	13.4
9	236.7	10.1	102.2	134.5	13.4
10	263.0	10.8	119.4	143.6	13.3
11	289.3	11.6	137.0	152.3	13.2
12	315.6	12.3	155.1	160.5	13.1
13	341.9	12.9	173.6	168.3	13.1
14	368.2	13.4	192.6	175.6	13.1
15	394.5	13.9	211.9	182.6	13.1
16	420.8	14.3	231.4	189.3	13.2
17	447.1	14.8	251.1	196.0	13.3
18	473.4	15.2	271.0	202.4	13.3
19	499.7	15.6	290.9	208.8	13.4
20	527.6	16.1	312.3	215.4	13.4

Exhibit 6-6. Oil production, CO_2 injection, and CO_2 production; CO_2 Prophet modeling of the CO_2 flood, Horn Mountain oil field NFB M sand; (985 acres, Sor 32.5%, DP = 0.5)

Year	CO₂Inj (Bcf)	Oil Prod (MMbbls)	CO₂ Prod (Bcf)	Purch CO₂ (Bcf)	CO₂ Util (Mcf/bbl)
1	26.3	1.2	0.0	26.3	22.8
2	52.6	2.6	0.1	52.5	20.0
3	78.9	4.4	2.6	76.3	17.5
4	105.2	6.1	8.2	97.0	16.0
5	131.5	7.7	16.2	115.3	15.0
6	157.8	9.2	25.9	131.9	14.3
7	184.1	10.6	37.0	147.1	13.8
8	210.4	11.9	49.3	161.1	13.5
9	236.7	13.2	62.6	174.1	13.2
10	263.0	14.3	76.6	186.4	13.0
11	289.3	15.5	91.2	198.1	12.8
12	315.6	16.5	106.5	209.1	12.7
13	341.9	17.5	122.3	219.6	12.5
14	368.2	18.4	138.7	229.5	12.5
15	394.5	19.3	155.5	239.0	12.4
16	420.8	20.1	172.7	248.1	12.3
17	447.1	20.9	190.0	257.1	12.3
18	473.4	21.8	207.6	265.8	12.2
19	499.7	22.5	225.4	274.3	12.2
20	527.6	23.4	244.6	283.0	12.1

7 COMPARATIVE ANALYSIS OF GEM AND CO₂ Prophet Modeling of CO₂ Flood, Horn Mountain Oil Field NFB M Sand

Based on the information provided in Section 5 and Section 6, the study found that the CO_2 Prophet Model was able to reasonably represent the performance of the CO_2 flood modeled using the more sophisticated GEM compositional simulator. Exhibit 7-1 provides a comparison of the results for the Horn Mountain oil field NFB M Sand from the two reservoir models. The DP reservoir heterogeneity values of 0.5 to 0.75 used in the CO_2 Prophet Model provide results that bracket the performance of the CO_2 flood in scenarios 1–3 calculated using GEM. Appendix B provides additional data and information comparing annual oil production from the GEM and the CO_2 Prophet models (more details provided in Appendix B).

Exhibit 7-1. Comparative assessments of performance for the Horn Mountain oil field NFB M Sand

Parameter	CO	Flood Performa GEM	nce	erformance let Model				
	Scenario 1	Scenario 2	Scenario 3	DP = 0.75	DP = 0.5			
OOIP (MMbbls)	154	154	154	154	154			
CO ₂ Injection (Bcf)	526	526	526	528	528			
CO ₂ Production (Bcf)	255	268	264	312	245			
CO₂ Storage (Bcf)	271	258	262	215	283			
Cumulative Oil Recovery								
MMbbls	19.2	15.5	22.5	16.1	23.4			
% of OOIP	12.5%	10.1%	14.6%	10.5%	15.2%			
CO₂/Oil Ratio (Mcf/bbl)								
Gross	27.4	33.9	23.4	32.8	22.6			
Net	14.1	16.6	11.6	13.4	12.1			

In addition to the three scenarios discussed above, the study examined the more capital-intensive Scenario 4, involving drilling three new CO₂ injection wells and shutting in the inactive A6 water injection well. While this scenario provided the largest volume of incremental oil recovery and CO₂ storage, it requires information beyond the data in the Bureau of Ocean Energy Management database and reservoir modeling sophistication beyond the current capabilities of the CO₂ Prophet Model.

8 REFERENCES

- [1] National Energy Technology Laboratory, "StrmtbFlow Fortran Program," U.S. Department of Energy, 31 October 2019. [Online]. Available: https://netl.doe.gov/energy-analysis/details?id=3940. [Accessed 9 June 2020].
- [2] National Energy Technology Laboratory, "StrmtbGen Fortran Program," U.S. Department of Energy, 31 October 2019. [Online]. Available: https://netl.doe.gov/energy-analysis/details?id=3939. [Accessed 9 June 2020].
- [3] V. Kuuskraa, A. Oudinot and M. Wallace, "Cognac Offshore Oil Field Case Study," U.S. Department of Energy, National Energy Technology Laboratory, Pittsburgh, PA, 2020.
- [4] V. Kuuskraa, A. Oudinot and M. Wallace, "Petronius Offshore Oil Field Case Study," U.S. Department of Energy, National Energy Technology Laboratory, Pittsburgh, PA, 2020.
- [5] Bureau of Ocean Energy Management, "Outer Continental Shelf, Estimated Oil and Gas Reserves, Gulf of Mexico OCS Region," U.S. Department of the Interior, Bureau of Ocean Energy Management, Gulf of Mexico OCS Region, OCS BOEM 2020-028, 2018.
- [6] A. Milkov, E. Goebel, L. Dzou, D. Fisher, A. Kutch, N. McCaslin and D. Bergman, "Compartmentalization and time-lapse geochemical reservoir surveillance of the Horn Mountain oil field, deep-water Gulf of Mexico," AAPG Bulletin, vol. 91, no. 6, pp. 847-876, 9 January 2007.
- [7] Bureau of Ocean Energy Mangement, "Oil and Gas Operations Reports Part A (OGOR-A)," U.S. Department of the Interior, Undated. [Online]. Available: https://www.data.boem.gov/Main/OGOR-A.aspx. [Accessed 2019].
- [8] L. Li, J. J. Sheng and J. Xu, "Gas Selection for Huff-n-Puff EOR in Shale Oil Reservoirs Based upon Experimental and Numerical Study," Society of Petroleum Engineers, 2017.

APPENDIX A

This Appendix provides additional data and information on well by well production from the "first-order" history match.

Exhibit A-1. Annual Oil Production by Well vs. History Match -- NFB Horn Mountain (MMbbl)

	Well A2		Wel	Well A3		Well A4		Total NFB	
Year	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	
2003	3.09	3.09	2.55	2.55	3.09	3.09	8.73	8.73	
2004	2.50	2.51	3.52	3.53	3.05	3.05	9.07	9.09	
2005	2.11	2.11	2.82	2.82	2.49	2.49	7.42	7.42	
2006	2.29	2.29	2.66	2.66	2.39	2.39	7.34	7.34	
2007	2.10	2.10	1.40	1.40	2.05	2.05	5.54	5.54	
2008	2.25	2.26	0.69	0.69	1.70	1.71	4.64	4.66	
2009	1.94	1.94	0.55	0.55	1.54	1.54	4.04	4.04	
2010	1.30	1.30	0.17	0.17	1.45	1.45	2.92	2.92	
2011	0.62	0.62	0.26	0.26	0.94	0.94	1.83	1.83	
2012	0.69	0.69	0.18	0.18	1.02	1.02	1.89	1.90	
2013	1.06	1.06	0.03	0.03	1.14	1.14	2.22	2.22	
2014	1.00	1.00	0.11	0.11	1.18	1.18	2.29	2.29	
2015	0.82	0.82	0.10	0.10	1.00	1.00	1.93	1.93	
2016	0.78	0.78	0.03	0.03	0.96	0.97	1.77	1.78	
2017	0.73	0.73	0.00	0.00	0.89	0.89	1.61	1.61	
2018	0.61	0.61	0.00	0.00	0.85	0.85	1.46	1.46	
Total	23.89	23.91	15.08	15.09	25.74	25.76	64.71	64.75	

Exhibit A-2. Annual Gas Production by Well vs. History Match -- NFB Horn Mountain (Bcf)

	Well A2		We	Well A3		Well A4		Total NFB	
Year	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	
2003	2.52	2.48	2.04	2.05	2.61	2.48	7.17	7.01	
2004	2.02	2.01	2.80	2.84	2.53	2.45	7.35	7.30	
2005	1.65	1.69	2.14	2.27	1.99	2.00	5.78	5.96	
2006	1.68	1.84	1.94	2.14	1.83	1.92	5.45	5.90	
2007	1.52	1.69	1.12	1.12	1.62	1.64	4.26	4.45	
2008	1.54	1.81	0.55	0.56	1.32	1.37	3.42	3.74	
2009	1.33	1.56	0.49	0.45	1.19	1.24	3.01	3.24	
2010	1.07	1.05	0.13	0.14	1.25	1.16	2.44	2.35	
2011	0.50	0.50	0.25	0.21	0.77	0.76	1.52	1.47	
2012	0.55	0.56	0.10	0.14	0.81	0.82	1.46	1.52	
2013	0.90	0.85	0.00	0.02	0.95	0.91	1.85	1.78	
2014	0.82	0.80	0.20	0.09	0.99	0.95	2.01	1.84	
2015	0.66	0.66	0.18	0.08	0.83	0.81	1.67	1.55	
2016	0.63	0.63	0.03	0.03	0.71	0.78	1.38	1.43	
2017	0.51	0.58	0.00	0.00	0.56	0.71	1.07	1.29	
2018	0.42	0.49	0.00	0.00	0.72	0.69	1.14	1.18	
Total	18.32	19.20	11.98	12.12	20.68	20.69	50.98	52.01	

Exhibit A-3. Annual Water Production by Well vs. History Match -- NFB Horn Mountain (MMbbl)

	Well A2		We	Well A3		II A4	Total NFB	
Year	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)	Actual (MMbbl)	History Match (MMbbl)
2003	0.00	0.08	0.00	0.07	0.00	0.08	0.01	0.23
2004	0.00	0.06	-	0.09	0.01	0.08	0.01	0.24
2005	0.01	0.05	0.02	0.10	0.08	0.06	0.11	0.22
2006	0.01	0.06	0.32	0.72	0.30	0.06	0.63	0.84
2007	0.06	0.05	0.82	0.78	0.46	0.42	1.34	1.26
2008	0.02	0.06	0.92	0.55	0.61	0.95	1.56	1.56
2009	0.16	0.05	1.18	0.55	0.69	1.21	2.03	1.81
2010	0.34	0.06	0.52	0.20	0.76	1.48	1.62	1.74
2011	0.24	0.09	0.79	0.32	0.64	1.09	1.67	1.50
2012	0.37	0.18	0.84	0.24	0.86	1.28	2.07	1.70
2013	0.63	0.36	0.14	0.04	1.05	1.50	1.82	1.90
2014	0.70	0.50	0.92	0.18	1.19	1.62	2.81	2.31
2015	0.69	0.61	0.92	0.17	1.14	1.43	2.74	2.20
2016	0.81	0.76	0.32	0.06	1.22	1.42	2.35	2.24
2017	0.83	0.90	0.00	0.00	1.10	1.36	1.93	2.26
2018	0.89	0.92	0.00	0.00	1.17	1.36	2.06	2.29
Total	5.77	4.81	7.71	4.07	11.28	15.40	24.76	24.28

APPENDIX B

This Appendix provides additional data and information comparing annual oil production from the GEM and the CO_2 Prophet models.

Exhibit B-1. Annual Incremental Oil Production -- GEM vs. CO2 Prophet (MMbbl)*

		GEM Model		CO2 Prop	het Model
Year	Scenario 1	Scenario 2	Scenario 3	DP = 0.75	DP = 0.50
1	2.0	2.0	2.0	1.3	1.2
2	2.2	2.1	2.4	1.7	1.4
3	2.1	2.1	2.5	1.5	1.8
4	1.9	1.8	2.2	1.1	1.7
5	1.8	1.5	2.2	1.1	1.6
6	1.6	1.4	2.1	1.0	1.5
7	1.5	1.2	1.8	0.9	1.4
8	1.3	0.9	1.5	0.8	1.3
9	1.1	0.7	1.1	0.7	1.3
10	0.9	0.4	0.8	0.7	1.1
11	0.7	0.3	0.7	0.8	1.2
12	0.5	0.3	0.6	0.7	1.0
13	0.4	0.3	0.6	0.6	1.0
14	0.3	0.2	0.5	0.5	0.9
15	0.3	0.1	0.4	0.5	0.9
16	0.2	0.0	0.5	0.4	0.8
17	0.2	0.2	0.4	0.5	0.8
18	0.1	-	0.2	0.4	0.9
19	0.1	-	0.1	0.4	0.7
20	0.0	-	0.1	0.5	0.9
Total	19.3	15.5	22.6	16.1	23.4

^{*}Totals may not add due to rounding





Exhibit B-2. Chart of Annual Incremental Oil Production -- GEM vs. CO₂ Prophet (MMbbl)





www.netl.doe.gov

Albany, OR \bullet Anchorage, AK \bullet Morgantown, WV \bullet Pittsburgh, PA \bullet Sugar Land, TX (800) 553-7681